

PLAST C SURF 1R 4M EC IP65 ABS



GARO's plastic consumer unit for surface mounting with rounded design with transparent, smoke-coloured door. The 2 - and 3-row enclosures have 150 mm spacing between the DIN rails with space for wiring under the rails. Module widths are adapted to components that are 17.5 mm wide. Enclosures are sealable and manufactured of halogen-free ABS plastic. GARO's plastic distribution cabinet for surface mounting with rounded design with transparent, smoke-coloured door. The 2 - and 3-row enclosures have 150 mm spacing between the DIN rails with space for wiring under the rails. Module widths are adapted to components that are 17.5 mm wide. Enclosures are sealable and manufactured of halogen-free ABS plastic. GARO's plastic distribution cabinet for surface mounting with rounded design with transparent, smoke-coloured door. The 2 - and 3-row enclosures have 150 mm spacing between the DIN rails with space for wiring under the rails. Module widths are adapted to components that are 17.5 mm wide. Plastic consumer unit surface mounting IP65 1 row max 4-modules ABS plastic.

E-number	Article number
2271138	110296

General properties

Type designation	NUPT 1-4 E
Rated voltage [V AC]	400
Frequency [Hz]	50
Degree of protection [IP]	65
Colour	Grey
Standard	EN 61439-3, EN 62208
Package size [pcs]	1
Materials	Plastic
Isolation voltage [V]	1000 V AC / 1500 V DC
Mounting method	Surface mounting
Impact strength	IK08
Locks	No
RAL-nummer	RAL7035

Specific properties

Name	PLAST C SURF 1R 4M EC IP65 ABS
E-number	2271138
Article number	110296
Modules [pcs]	4
Width [mm]	102
Height [mm]	177
Depth [mm]	105
Netweight [kg]	0.37
Connection PE [pcs] [mm ²]	Valbar N eller PE plint
Connection N [pcs]	1x(16-35mm ²)+5x(10-25mm ²)
Knockouts up[Ø/pcs]	1xM25
Rows [pcs]	1