

# PLAST C SURF 1R 4M IP65 ABS



GARO's plastic consumer unit for surface mounting with rounded design with transparent, smoke-coloured door. The 2 - and 3-row enclosures have 150 mm spacing between the DIN rails with space for wiring under the rails. Module widths are adapted to components that are 17.5 mm wide. Enclosures are sealable and manufactured of halogen-free ABS plastic. GARO's plastic distribution cabinet for surface mounting with rounded design with transparent, smoke-coloured door. The 2 - and 3-row enclosures have 150 mm spacing between the DIN rails with space for wiring under the rails. Module widths are adapted to components that are 17.5 mm wide. Enclosures are sealable and manufactured of halogen-free ABS plastic. GARO's plastic distribution cabinet for surface mounting with rounded design with transparent, smoke-coloured door. The 2 - and 3-row enclosures have 150 mm spacing between the DIN rails with space for wiring under the rails. Module widths are adapted to components that are 17.5 mm wide. Plastic consumer unit surface mounting IP65 1 row max 4-modules ABS plastic.

**E-number**                      **Article number**  
2271139                              110297

## General properties

Type designation	NUPT 1-4
Rated voltage [V AC]	400
Frequency [Hz]	50
Degree of protection [IP]	65
Colour	Grey
Standard	EN 61439-3, EN 62208
Package size [pcs]	1
Materials	Plastic
Isolation voltage [V]	1000 V AC / 1500 V DC
Mounting method	Surface mounting
Impact strength	IK08
Locks	No
RAL-nummer	RAL7035

## Specific properties

Name	PLAST C SURF 1R 4M IP65 ABS
E-number	2271139
Article number	110297
Modules [pcs]	4
Width [mm]	166
Height [mm]	231
Depth [mm]	113
Netweight [kg]	0.81
Connection PE [pcs] [mm <sup>2</sup> ]	1x(16-35mm <sup>2</sup> )+1x(4-10mm <sup>2</sup> )+3x(2,5-6mm <sup>2</sup> )
Connection N [pcs]	1x(16-35mm <sup>2</sup> )+1x(4-10mm <sup>2</sup> )+3x(2,5-6mm <sup>2</sup> )
Knockouts Down[Ø/pcs]	2xM25 - 1xM40
Knockouts up[Ø/pcs]	2xM25 - 1xM40
Rows [pcs]	1