

PLAST C SURF 1R 18M IP65 ABS



GARO's plastic consumer unit for surface mounting with rounded design with transparent, smoke-coloured door. The 2 - and 3-row enclosures have 150 mm spacing between the DIN rails with space for wiring under the rails. Module widths are adapted to components that are 17.5 mm wide. Enclosures are sealable and manufactured of halogen-free ABS plastic. GARO's plastic distribution cabinet for surface mounting with rounded design with transparent, smoke-coloured door. The 2 - and 3-row enclosures have 150 mm spacing between the DIN rails with space for wiring under the rails. Module widths are adapted to components that are 17.5 mm wide. Enclosures are sealable and manufactured of halogen-free ABS plastic. GARO's plastic distribution cabinet for surface mounting with rounded design with transparent, smoke-coloured door. The 2 - and 3-row enclosures have 150 mm spacing between the DIN rails with space for wiring under the rails. Module widths are adapted to components that are 17.5 mm wide. Plastic consumer unit surface mounting IP65 1 row max 18-modules ABS plastic.

E-number	Article number
2271143	110301

General properties

Type designation	NUPT 1-18
Rated voltage [V AC]	400
Frequency [Hz]	50
Degree of protection [IP]	65
Colour	Grey
Standard	EN 61439-3, EN 62208
Package size [pcs]	1
Materials	Plastic
Isolation voltage [V]	1000 V AC / 1500 V DC
Mounting method	Surface mounting
Impact strength	IK08
Locks	No
RAL-number	RAL7035

Specific properties

Name	PLAST C SURF 1R 18M IP65 ABS
E-number	2271143
Article number	110301
Modules [pcs]	18
Width [mm]	418
Height [mm]	286
Depth [mm]	148
Netweight [kg]	2.07
Connection PE [pcs] [mm ²]	1x(16-35mm ²)+1x(10-25mm ²)+8x(4-10mm ²)+8x(2,5-6mm ²)
Connection N [pcs]	1x(16-35mm ²)+1x(10-25mm ²)+8x(4-10mm ²)+8x(2,5-6mm ²)
Knockouts Down[Ø/pcs]	12xM20 - 6xM25 - 2xM32 - 1xM40
Knockouts up[Ø/pcs]	10xM20 - 6xM25 - 2xM32 - 1xM40
Rows [pcs]	1